

# WATER WELL BORE LOG



Well Owner Mike and Bertha Newman

Map Sheet No

Address 11022 Cowslip Valley

Locality

Waihopi Valley

Drilling Method Rotary D.T.H.H Tubex

Grid Reference

2574027  
5957689

Driller Shane Hogan/Rex Garton

NZGS Well No

P28w/3581

Drilling Date 20/10/99

FILE No.		Land Use Consent No*	
5 NOV 1999			
		ACTION	

Depth from Surface (m)	Description	Details of Aquifers		
		Depth of Surface (m)	Static Water Level (m)	
Top		Top	Bottom	
0	Water bearing inch rounds.			
10	Blue grey silty clay wet and thick.			
12.5	Yellow brown silty clay gravels. Subangular and subrounded. Fine to course. Moderately sorted. Sticky.			
19.6	Gravels as at 12.5 - 19.6. Yielding very little water. Gravels clearer, less silty clay.			
21.8	Yellow brownish clay and fine peastone. Slightly plastic. Firm drilling (high rotation speed)			
22.8	Fine gravels. Clean subangular and rounded bearing water, a hint of blue grey silty gravels.			
26.1	Blue grey clay moist and slighty plastic.			
33.2	Blue grey clay moist and slighty plastic with some fine peastone. Blue grey clay moist and slighty plastic moderate penetration high rotation speed.			
35.6	Blue grey clay moist and slighty plastic moderate penetration high rotation speed.			
{ 1.2 metre difference in non-pumping or static water level between this well and the shallower well 5 metres away. }				

FILE No.:
OFFICER:
DATE RECV'D
25 JAN 2000
MARLBOROUGH DISTRICT COUNCIL

Phone (03) 384 1255 - Fax (03) 384 1386 - eMail [texco@ihug.co.nz](mailto:texco@ihug.co.nz) - 61a Chapmans Rd, Christchurch 8002

Texco Crushing/Texco Remediation/Texco Quarry/Texco Drilling are associated companies of Townshend Excavating Ltd  
Customers please note: All potential hazards, as per the Occupational Safety & Health Regulations, must be clearly identified to Texco before work commences.

# WATER WELL BORE LOG



Well Owner     Mike and Bertha Newman

Map Sheet No

Address 11022 Cowslip Valley

Locality                      Waihopi Valley

Drilling Method Rotary D.T.H.H Tubex

Grid Reference

Driller Shane Hogan/Rex Garton

NZGS Well No

Drilling Date 20/10/99

**5 NOV 1999**

Strata		Details of Aquifers	
Depth from Surface (m)	Description	Depth of Surface (m)	Static Water Level (m)
Top	0 Water bearing inch rounds.	Top	Bottom
10	Blue grey silty clay wet and thick.		
12.5	Yellow brown silty clay gravels. Subangular and subrounded. Fine to course. Moderately sorted. Sticky.		
19.6	Gravels as at 12.5 - 19.6. Yielding very little water. Gravels clearer, less silty clay.		
21.8	Yellow brownish clay and fine peastone. Slightly plastic. Firm drilling (high rotation speed)		
22.8	Fine gravels. Clean subangular and rounded bearing water, a hint of blue grey silty gravels.		
26.1	Blue grey clay moist and slighty plastic.		
33.2	Blue grey clay moist and slighty plastic with some fine peastone. Blue grey clay moist and slighty plastic moderate penetration high rotation speed.		
35.6	Blue grey clay moist and slighty plastic moderate penetration high rotation speed.		

FILE No.:  
OFFICER:  
DATE  
RECV'D 25 JAN 2000  
MARLBOROUGH  
DISTRICT COUNCIL

Phone (03) 384 1255 - Fax (03) 384 1386 - eMail [texco@ihug.co.nz](mailto:texco@ihug.co.nz) - 61a Chapmans Rd, Christchurch 8002

Texco Crushing/Texco Remediation/Texco Quarry/Texco Drilling are associated companies of Townsend Excavating Ltd  
Customers please note: All potential hazards, as per the Occupational Safety & Health Regulations, must be clearly identified to Texco before work commences



Drilling Date 21.08.00

FILE No.: W 000570  
OFFICER: HW  
DATE REC'D 08 SEP 2000  
MARLBOROUGH  
DISTRICT COUNCIL



Map Sheet Number

### Grid Reference

NZGS Well No

Land Use Consent No

By Owner

By Owner

By Owner

By Owner

Strata		Details of Aquifers		
Depth from Surface (m)	Description	Depth from Surface (m)		Static Water Level (m)
Top GL		Top	Bottom	
35.60	BLUE GRAY CLAY			
36.50	SMALL BROWN GRAVEL WITH MODERATE CLAY			
43.00	GREY CLAY WITH GRAVEL			
48.00	YELLOW BROWN CLAY FINE GRAVELS			
50.00	BROWN CLAY HARD AND DRY			
53.50	CLAY BOUND ROCK			
	NB: PULLED BACK TO 36.00M. DEVELOPE WITH AIR FOR 3.00HRS NO USABLE WATER FOUND. ALL CASING REMOVED FROM WELL. WELL ABANDONED.			

Casing Diameter (mm) \_\_\_\_\_ Screen Length (m) \_\_\_\_\_

Well Depth Slot Size

Final Water Level Leader &amp; Diameter

Screen Type \_\_\_\_\_ Set At \_\_\_\_\_

CC:	CLIENT:	X
	REGIONAL COUNCIL:	X
	OFFICE X TWO:	X

Phone (03) 384 1255 - Fax (03) 384 1386 - eMail [dig@texco.co.nz](mailto:dig@texco.co.nz)

61a Chapmans Rd, Christchurch - PO Box 19641, Woolston, Christchurch 8030

Texco Crushing/Texco Remediation/Texco Quarry/Texco Drilling are associated companies of Townshend Excavating Ltd

Customers please note: All potential hazards, as per the Occupational Safety & Health Regulations, must be clearly identified to Texco before work commences.



FILE No.:  
OFFICER: H W  
DATE 08 SEP 2000  
REC'D  
MARLBOROUGH  
DISTRICT COUNCIL



Drilling Date 21.08.00

Land Use Consent No

By Owner

Strata		Details of Aquifiers		
Depth from Surface (m)	Description	Depth from Surface (m)		Static Water Level (m)
Top GL		Top	Bottom	
35.60	BLUE GRAY CLAY			
36.50	SMALL BROWN GRAVEL WITH MODERATE CLAY			
43.00	GREY CLAY WITH GRAVEL			
48.00	YELLOW BROWN CLAY FINE GRAVELS			
50.00	BROWN CLAY HARD AND DRY			
53.50	CLAY BOUND ROCK			
	NB: PULLED BACK TO 36.00M. DEVELOPE WITH AIR FOR 3.00HRS NO USABLE WATER FOUND. ALL CASING REMOVED FROM WELL. WELL ABANDONED.			

Screen Type Set At

CC:	CLIENT:	X
	REGIONAL COUNCIL:	X
	OFFICE X TWO:	X

Customers please note: All potential hazards, as per the Occupational Safety & Health Regulations, must be clearly identified to Texco before work commences.



M+B. NEWMAN  
RD 6.  
BLEN.

7360

SHEET P. 28.

1:10,000.

== TITLE BOUNDARIES

OMAKA R.

TINTSFIELD RD

5701.

E. 5701

existing wall

2

150M

A

existing wall

12

HOUSE.

B

Span's Cr.

N 7360